



Chemical World MGUS, LLC

Product Data Sheet

EPOXY RESIN SM601RX75 (Solvent-based)

EPOXY RESIN SM601RX75 is mixed by SM828 and Xylene (75:25), it has low viscosity, good liquidity, easy to operate, it is suitable for the preparation of solvent-based coating, dipping, concrete cement, paint, glass fiber reinforced plastic composite materials, adhesives, etc.

Typical Properties:

ITEM	STANDARD DATA
Appearance	Transparent Liquid
Epoxy Equivalent g/eq	450-500
Viscosity mPa.s/25°C	8000-15000
Color Gardner	0.5max
Total Chlorine ppm	1400max
Hydrolyzable Chloride ppm	500max
Inorganic Chlorine ppm	5max
Solid content %	75±1
Solvent	xylene

Packing: This Liquid epoxy resin is supplied in bulk or in 200 kg tight-head drums. should be stored in dry conditions away from sources of heat, preferably in the original containers kept tightly closed. Under these conditions and at normal temperatures the storage life should be at least two years.

CHEMICAL WORLD MGUSS 7600 Burr Ferry Dr., McKinney Texas, USA,
75071. Tel. +1-(972)-795.1918. e-mail: f.infante@chemicalworldmgus.com